Premium Water Heaters











The Albin Pump Marine Premium Water Heaters and square models have a toxic free ceramic inside coating to ensure highest water quality over time. Dual heating as standard - electrical heating and indirect heating based on an second heat source, for example based on the cooling system from the Marine engine or generator set.

- Round version 22 liter (5.8 gal), 30 liter (8 gal), 45 liter (12 gal), 60 liter (17 gal)
- Rectangular version 20 liter (5.6 gal)
- Interchangeable with common brands such as Webasto/Isotemp
- 850W, 230V or 800W, 120V
- Doubly enamaled steel tank with aluminium outer coating
- Enamaled iron heat exchanger for indirect heating from e.g. engine cooling water
- Incoloy corrosion-resistant alloy elements for electrical heating
- Heat loss 1 °C (1.8 °F)/hour over 24 hours
- Flexible mounting brackets, thermostat and drain valve are included
- Designed for continuous use onboard vessels in demanding environments

Premium Rectangular Water Heater 20L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-01-005	850W	20 L (5.3 gal) Heats up 20L (5,6 gal) in 45min, good for	230V - 50 Hz	274	Fixed port connections BSP ½"	536 x 190 x 420 mm	12.5 Kg
08-01-028	800W	30L of mixed warm water or a 3 minute shower.	120V - 60 Hz	3.7 A	Fixed port connections NPT ½"	(21.1 x 7.5 x 16.5 in)	(28 lbs)

Premium Water Heater 22L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-01-001	850W	22 L (5.8 gal) Heats up 22L (5,8 gal) in 1h, good for 35L of	230V - 50 Hz	274	Fixed port connections BSP ½"	423.5 x 390 x 404 mm	11 Kg
08-01-024	800W	mixed mixed warm water or a 3,5 minute shower.	120V - 60 Hz	3.7 A	Fixed port connections NPT ½"	(16.7 x 15.4 x 15.9 in)	(24 lbs)

Premium Water Heater 30L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-01-002	850W	30 L (7.9 gal) Heats up 30L (8 gal) in 1,5h, good for 45L	230V - 50 Hz	274	Fixed port connections BSP ½"	503.5 x 390 x 404 mm	12 Kg
08-01-025	800W	of mixed warm wa- ter or a 4,5 minute shower.	120V - 60 Hz	3.7 A	Fixed port connections NPT ½"	(19.8 x 15.4 x 15.9 in)	(26 lbs)

Premium Water Heater 45L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-01-003	850W	45 L (11.9 gal) Heats up 45L (12 gal)	230V - 50 Hz	274	Fixed port connections BSP ½"	663.5 x 390 x 404 mm	14 Kg
08-01-026	800W	in 2h, good for 65L of mixed warm water or a 6,5 minute shower	120V - 60 Hz	3.7 A	Fixed port connections NPT ½"	(26.1 x 15.4 x 15.9 in)	(31 lbs)

Premium Water Heater 60L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-01-004	850W	60 L (15.8 gal) Heats up 60L (16 gal)	230V - 50 Hz	274	Fixed port connections BSP ½"	823.5 x 390 x 404 mm	16Kg
08-01-027	800W	in 4h, good for 90L of mixed warm water or a 9 minute shower	120V - 60 Hz	- 3.7 A	Fixed port connections NPT ½"	(32.4 x 15.4 x 15.9 in)	(35 lbs)



Premium Water Heaters






Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-01-032	850W	22 L (5.8 gal) Heats up 22L (5,8 gal) in 45min, good for	230V - 50 Hz	274	Fixed port connections BSP ½"	493 x 320 x 320 mm	11 Kg
08-01-030	800W	30L of mixed warm water or a 3 minute shower	120V - 60 Hz	3.7 A	Fixed port connections NPT ½"	(19.4 x 12.6 x 12.6 in)	(241bs)

The Albin Pump Marine Premium Water Heaters and square models have a toxic free ceramic inside coating to ensure highest water quality over time. Electrical heating only.

- Interchangeable with common brands such as Webasto/Isotemp
- 850W, 230V or 800W, 120V
- Doubly enamaled steel tank with aluminium outer coating
- Electric heating only 230V or 120V, for outboard boats or boats with genset, requires power AC 230V
- Incoloy corrosion-resistant alloy elements for electrical heating
- Heat loss 1°C (1.8°F)/hour over 24 hours
 - Flexible mounting brackets, thermostat and drain valve are included



Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-03-032	850W	20 L (5.3 gal) Heats up 22L (5,8 gal) in 45min, good for 30L of mixed warm	230V - 50 Hz		Fixed port connections BSP ½"		
08-03-030	800W	water or a 3 minute shower. Keeps heated water warm for a duration >10h when not connected to shore power.	120V - 60 Hz	3.7 A	Fixed port connections NPT ½"	493 x 320 x 320 mm (19.4 x 12.6 x 12.6 in)	11 Kg (24 lbs)







Stainless Steel Water Heaters











The Albin Pump Marine Stainless Steel Water Heaters have a stainless steel AISI 316 tank, anti-corrosion treatment with pickling and passivation. Dual heating as standard - electrical heating and indirect heating based on an second heat source, for example based on the cooling system from the Marine engine or generator set.

- Round version 22 liter (5.8 gal), 30 liter (8 gal), 45 liter (12 gal), 60 liter (17 gal)
- Interchangeable with common brands such as Webasto/Isotemp
- 850W, 230V
- Enamaled iron heat exchanger for indirect heating from e.g. engine cooling water
- Incoloy corrosion-resistant alloy elements for electrical heating
- Heat loss 1 °C (1.8 °F)/ hour over 24 hours
- Flexible mounting brackets, thermostat and drain valve are included
- Designed for continuous use onboard vessels in demanding environments

Stainless Steel Water Heater 22L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-02-006	850W	22 L (5.8 gal) Heats up 22L (5,8 gal) in 1h, good for 35L of mixed mixed warm water or a 3,5 minute shower.	230V - 50 Hz	3.7 A	Fixed port connections BSP ½"	439.5 x 390 x 404 mm (17.3 x 15.4 x 15.9 in)	11 Kg (24 lbs)

Stainless Steel Water Heater 30L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-02-007	850W	30 L (7.9 gal) Heats up 30L (8 gal) in 1,5h, good for 45L of mixed warm wa- ter or a 4,5 minute shower.	230V - 50 Hz	3.7 A	Fixed port connections BSP ½"	503.5 x 390 x 404 mm (19.8 x 15.4 x 15.9 in)	12 Kg (26 lbs)

Stainless Steel Water Heater 45L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-02-008	850W	45 L (11.9 gal) Heats up 45L (12 gal) in 2h, good for 65L of mixed warm water or a 6,5 minute shower	230V - 50 Hz	3.7 A	Fixed port connections BSP ½"	689 x 390 x 404 mm (27.1 x 15.4 x 15.9 in)	14 Kg (31 lbs)

Stainless Steel Water Heater 60L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-02-009	850W	60 L (15.8 gal) Heats up 60L (16 gal) in 4h, good for 90L of mixed warm water or a 9 minute shower	230V - 50 Hz	3.7 A	Fixed port connections BSP ½"	849 x 390 x 404 mm (33.4 x 15.4 x 15.9 in)	16 Kg (35 lbs)

Stainless Steel Water Heater 80L

Part no.	Power	Capacity	Voltage	Fuse size	Connections	Dimensions LxWxH	Weight empty
08-02-010	850W	80 L (21.2 gal) Heats up 80L (21,2 gal) in 5h, good for 120L of mixed warm water or a 15 minute shower		3.7 A	Fixed port connections BSP ½"	1009 x 390 x 404 mm (39.7 x 15.4 x 15.9 in)	20 Kg (44 lbs)




Accessories/ Spare Parts









Complement your Water Heaters with Albin Pump Marine Mixer and Hose Connection Kits and Spare Parts.

Premium Water Heater Mixer Kit

Premium Mixer Kit, safe distribution of mixed warm water at exact temperatures.

· Allows you to not waste any hot water which saves water and energy

Part no.	Description
08-66-011	Premium Mixer Kit

Hose Connection Kit

Part no.	Description	
08-66-012	Hose Connection Kit	

Pressure Release Valve

Safely realeases excess pressure and also for draining the water heater.

Part no.	Description	
08-99-013	Pressure Release Valve	

Drain valve

Simplify the draining of the water heater of its water

• To avoid freezing or to preserve the water heater off season

Part no.	Description
08-99-014	Drain valve

Replacement Heater Elements

Heater elements that fit all Albin Pump Marine water heaters

Heater Element 550W/500W

Part no.	Description	Туре
08-99-015	Heater Element 230V 550W	550W allows to use the water heater at 230V with 4A shorepower fuse
08-99-018	Heater Element 120V 500W	500W allows to use water heater at 120V with 5A fuse



Accessories/ **Spare Parts**









Heater Element 850W/800W

Part no.	Description	Туре
08-99-016	Heater Element 230V 850W	850W allows to use water heater at 230V with 5A shorepower fuse
08-99-019	Heater Element 120V 800W	800W allows to use water heater at 120V with 10A shorepower fuse

Heater Element 1250W/1200W

Part no.	Description	Туре
08-99-017	Heater Element 230V 1250W	1250W allows to use water heater at 230V with 10A shorepower fuse
08-99-020	Heater Element 120V 1200W	1200W allows to use water heater at 120V with 15A shorepower fuse

Thermostat

Part no.	Description	Туре
08-99-021	Thermostat to set temperature of heated water.	Adjustable 40° – 80° C (104° – 176° F)

Premium Anode Short

Part no.	Description	Туре
08-99-022	Short anode for Premium Water Heater	Premium Water Heaters 20 – 30 L (5.3 – 7.9 gal)

Premium Anode Long

Part no.	Description	Туре
08-99-023	Long anode for Premium Water Heater	Premium Water Heaters 45 – 60 L (11.9 – 15.8 gal)

